

Data Sheet

C-Series H2-Sensor Analog

Magnetostrictive Linear Position Sensors

Document Part No. 551397 Revision A




- Contactless measurement entirely wear-free
- Low weight ideal for small portable OEM products
- Cost-efficient
- Space-saving
- Low energy requirement can be operated from 5 VDC or 12 VDC supply
- No wear no need for periodic re-adjustment
- Available with various position magnets
- Optional: direct or inverse analog output signal
- Optional: assignment of output signal to measuring length

The sensor is a function of the customer requirements according to the application, and considering the environment, environmental influences, including EMI protection effects.

Magnetostriction

The absolute Temposonics linear position sensors are based on the proprietary magnetostrictive measuring principle. This combines various magneto-mechanical effects and uses the physically exact velocity measurement of an ultrasonic wave (torsion pulse in its sensor element) for position detection. The sensor-integrated signal processing converts the measured values directly into commercially available outputs. The non-contact principle - an external moving magnet marks the position - eliminates the problems of wear, noise and false signals and guarantees best durability without recalibration.





Technical Data

ı	n	n	ш	t
ı	ш	μ	u	L

Measured variables: Position

Stroke length: 72, 109, 128, 148, 162, 186, 194, 217, 250 mm

Output

Analog: 0.1 - 4.9 VDC
Resolution: analog output signal
Signal without magnet not specified

Feature: At 5 VDC operating voltage output is ratiometric to operating voltage

Accuracy

Linearity: ± 0.15mm by means of magnet 401842, between 5% and 95% of stroke length

Zero tolerance: ± 1 mm

Hysteresis: ± 25µm

Repeatability: ± 25µm

Temperature variation: ± 0.005%

Temperature variation: \pm 0.005% per °C Update time: \pm 500 Hz (2 ms)

Operation conditions

Operating temperature: -40 °C...+75 °C (105 °C after consulting Temposonics)

Storage temperature: -20 °C...+85 °C

Pressure

up to 2500 m altitude IP Protection

IP

6 - DIN 40 050 Part 9 - Protection against foreign bodies: dustproof, complete protection against contact

7 - DIN 40 050 Part 9 - Protection against water - Temporary immersion

Environmental testing

Shock test: IEC-68-2-27

10g (11ms) -> Single hit 10g (11ms) 1000 shocks per axis

Vibration test: IEC 60068-2-6 (10...2000 Hz) 10g Sinus (resonance frequencies excluded)

EMC-test: Electromagnetic emission EN 61000-6-4

CISPR 16-2-3-Disturbance field strength (measuring distance 3 m)

CISPR 16-2-1-Disturbance current (DC voltage supply)

Electromagnetic immunity EN 61000-6-2 EN 61000-4-2 - Electrostatic discharge (ESD)

EN 61000-4-3 - Radiated electrosolenoidic radio frequency, free radiated

EN 61000-4-4 - Electrical fast transient (Burst)

EN 61000-4-5 - Surge

EN 61000-4-6 - Conducted radio-frequency, line guided EN 61000-4-8 - Power frequency solenoidic field

The sensor is a function of the customer requirements according to the application, and considering the environment, environmental influences, including EMI protection effects.

Form factor, material

Housing: Stainless steel 1.4404
Protective pipe: Stainless steel 1.4404

Electrical connection

Supply voltage: CS: 5 VDC (tolerance range 4.75 - 5.5 VDC), CM: 12 VDC (tolerance range 9 - 15 VDC)

Max. power consumption: max. 40 mA

Output load: \Rightarrow analog: \Rightarrow = 10 kg

Overvoltage protection: CS: up to 19 VDC short term CM: up to 29 VDC short term

Polarity protection: VDC - GND

Operating voltage quality: 5 VDC 12 VDC:

Grid control: \pm 0.05 % \pm 0.05 % for Ua at la 0 - 100 % Ripple: < 50 mVpp < 100 mVpp for Ua at Uemin - Uemax

Pin Signal


White DC Ground

Brown Output signal

Green Supply voltage

Silver GND


Mechanical connection



Accessories


Ring magnets


Description	Article No.	Inside Ø	Outside Ø	Width
Ring magnet 6 mm	401842	6.5 mm	9 mm	9 mm
Ring magnet 19.3 mm	400424	19.3 mm	28 mm	4.9 mm
Ring magnet 13.5 mm	254012	13.5 mm	20 mm	10.5 mm



<u>Float</u>


Description	Article No.	Inside Ø	Outside Ø	Width
Float 1	201611	9.5 mm	28.6 mm	30 mm
Float 2	201656	6 mm	22 mm	32 mm





Temposonics® Ordering

Ordering Information



Housing H2 = IP67 housing

Example:

CM186AVH2 Sensor

Sensor model C - Supply voltage 12 VDC - Measuring length 186 mm - Output analog - Housing IP67

Magnet and float options (An additional quantity of 1 unit per sensor should be ordered)

Description	Function	Article No.	
Ring magnet 6 mm	standard	401842	
Ring magnet 19.3 mm	optional after approval for applications requiring a magnet with more clearance	400424	
Ring magnet 13.5 mm	optional after approval for applications requiring a magnet with more clearance	254012	
Float 1 with magnet	optional after approval for applications	201611	
Float 2 with magnet	optional after approval for applications	201656	
IP67 - Protection-kit			
Protection-kit	electronic housing, O-ring	253525	
Protective pipe with flange	two-hole flange/order tube length with information - XXX	253526-XXX	

Application examples:

The target in customer solutions is a high degree of efficiency and synergy to the product. During the design phase measurements need to be taken which enable the product to meet customer requirements suitable for the application.

In this respect, close cooperative partnership between the customer and Temposonics is desirable.

All constructive measures relating to operating parameters (vibration, temperature and ESD) require consultation with Temposonics. This also includes the CE marking of components used for installation.



Level measurement in medical technology

An analyser for immunodiagnostics applications uses magnetostrictive level sensors in containers to monitor the levels of consumables and of the collected waste products of the analysis. Through continuous measurement, it is always known how much fluid is in the containers. This enables continuous reloading without interruption of the analysis and anticipatory planning.



Increased dosing accuracy, reduced consumption

The dosing accuracy during preparation of damping solution and precise control of the IPA concentration are of considerable importance for the production and process stability in printing systems. The continuous discussion relating to the toxic load of the ambient air at work places and the need for cost reduction in printing companies also requires further reduction of isopropyl alcohol in the damping solution. The Temposonics® OEM-sensor plays an important part for dosing of damping solutions and thus for decreasing the overall costs.



Position feedback in process measurement and control systems

The valve position feedback combines well-proven sensor technology and state-of-the-art design for optimized applications.

Our development activity focused on the requirements and wishes expressed by our customers in the liquid processing industry.

In addition to safe control and monitoring of all functions of process valves in breweries, dairies, facilities for production of fruit juice and production plants in the pharmaceutical industry, the C series provides a high degree of efficiency.



Position feedback in steering systems

The customer-specific sensors are used to monitor the steering position of rear drives and to provide position feedback. Based on the linear C-series position sensor, these sensors are equipped with a special housing, which was developed by the end user and realized by Temposonics. The sensors measure the stroke of steering cylinders on the port side and the bow side. Typically installed in multi-engine boats, the boat control system uses the sensor signal to permit control of the boat movement using a joystick: A solution termed "Steer-By-Wire".



Cabin suspension

To reduce the human vibration, directive 2002/44/EC (human vibration directive) of the European Union has been implemented into national law in March 2007. This directive defines binding limit values (reference period of 8 hours < value 0.5m/s²) for the hand-and-arm area as well as whole-body vibration values, which must not be exceeded.

These limit values are met by effectively reducing the induced vehicle vibration using C-series position sensors in a cabin suspension system.

The cabin suspension system permits reduction of the accelerations mainly in the Z axis. Due to this reduction, the vibration load acting on the driver is alleviated considerably, without affecting driving experience and operability.

Document Part Number: 551397 Rev. A (EN) 04/2013

© 2021 Temposonics, LLC – all rights reserved. Temposonics, LLC and Temposonics GmbH & Co. KG are subsidiaries of Amphenol Corporation. Except for any third party marks for which attribution is provided herein, the company names and product names used in this document may be the registered trademarks or unregistered trademarks of Temposonics, LLC or Temposonics GmbH & Co. KG. Detailed trademark ownership information is available at www.temposonics.com/trademarkownership.

temposonics.com

UNITED STATES Temposonics, LLC Americas & APAC Region

3001 Sheldon Drive Cary, N.C. 27513 Phone: +1 919 677-0100 E-mail: info.us@temposonics.com

GERMANY Temposonics GmbH & Co. KG EMEA Region & India

Auf dem Schüffel 9 58513 Lüdenscheid Phone: +49 2351 9587-0 E-mail: info.de@temposonics.com